


- NOTES -  
 ALL VOLTAGES MEASURED WITH VTVM FROM CHASSIS GROUND  
 WITH NO SIGNAL INPUT AND WITH CONTROLS SET AS FOLLOWS:  
 SQUELCH - MAXIMUM CW  
 A.N.L. - ON  
 SELECTIVITY - BROAD  
 VOLUME - ANY POSITION  
 FUNCTION - MANUAL  
 R.F. GAIN - MAXIMUM CW  
 AVC - ON  
 UNLESS OTHERWISE SPECIFIED ALL RESISTORS ARE 1/2 WATT  
 CAPACITOR VALUES IN WHOLE NUMBERS ARE MICRO-MICRO  
 FARADS.  
 CAPACITOR VALUES IN DECIMALS ARE MICRO FARADS.  
 T2, T3, T4, T5, T6, T7 IF CANS - 455 KC  
 TOP SLUG TUNES GRID CIRCUIT  
 BOTTOM SLUG TUNES PLATE CIRCUIT  
 OUTLINED CONTROLS ARE ON FRONT PANEL EXAMPLE -  
 FUNCTION

**BROWNING LABORATORIES**  
 LACONIA  N.H., U.S.A.  
**R-27 SCHEMATIC**  
 DRAWN BY G.A.T. 3-28-64 CHECKED BY *A.S.V.*  
 ISSUED 3/9/64 DWG. A-419 R-3

2-4-64 Revised  
 7-23-64 Rev. 100  
 10-4-64 Rev. 100